

MEXCLOSED 44 A Film Forming Substance Intended for the Treatment of Closed Loop Systems

DESCRIPTION

Mexel is a completely different way of looking at the treatment of systems that utilize water for heating and cooling applications. Unlike traditional water treatment programs that treat the water itself, Mexel is a surface treatment that protects the system from the water. By forming a protective barrier, utilizing Mexel's film forming amine technology, we are able to prevent scale and corrosion all with one product.

MEXCLOSED 44 is a filming amine based product utilizing the Mexel surface treatment technology. MexClosed 44 will restore and maintain the highest level of efficiency by effectively controlling scale, corrosion, and deposits.

APPLICATIONS/USE

- A nitrite free closed loop treatment utilizing the Mexel surface treatment technology providing both scale and corrosion protection
- Effective in the removal of existing corrosion and scale deposits in problematic closed loop systems
- General dispersant for mud and silt
- All organic formula drastically reduces the chemistry effect on the system conductivity

The amount of MexClosed 44 dosed, for proper treatment of the closed loop system, is 200ppm. Taking into account the detergency effect of this product, it is recommended that an adequate system filter be installed to remove any residual debris, or an agreement is made between end user and supplier before treatment that the system may need to be dumped, rinsed, and re-treated in an effort to remove residual debris. The residual concentration must be maintained between 5 and 10 ppm. MexClosed 44 is not recommended for use in systems containing Aluminum.

STORAGE & HANDLING

The MexClosed 44 is a basic product. It must be handled with the precautions of use for the industrial chemicals. Avoid the contacts with the skin and the eyes. Wearing of glasses and gloves recommended. **Available in:** 5 Gal, 15 Gal, 30 Gal, 55 Gal, 275 Gal, 330 Gal, Bulk

PRODUCT DATA SHEET



IMPORTANT PRODUCT INFORMATION

Composition	Film Forming Substance
Aspect	Off White Liquid
Odor	Characteristic Amine
рН	11
Density	0.98

SAFETY REMINDER: Consult product label and Safety Data Sheet (SDS) before use. SDS's available by request.

IMPORTANT: Refer to the SDS for further health, safety and environmental information regarding this product. Information and recommendations in this bulletin are based on information believed to be reliable. However, the use of the product is beyond the control of GWT, and no guarantee, expressed or implied, is made as the effects of such the results to be obtained if not used in accordance with directions or stabled safe practice. The buyer must assume all responsibility, including injury or damage, resulting from misuse of the product as such, or in combination with other material.

INFOTRAC 24 HOUR EMERGENCY 800.535.5053

DATE ISSUED: 11/12/2020



354 West Armory Drive, South Holland, IL 60473 | 708.349.9991 Fax 708.349.9995 | info@gwt-inc.com | www.gwt-inc.com